



F-11 LINE INTERACTIVE UPS

650VA / 1200VA / 2200VA

ION F-11 is a general purpose line interactive UPS that offers protection from power surges and failures in the home, office or small business. Ideally suited to protecting computers and POS devices the ION F-11 provides clean, reliable power delivery. Presented in a stylishly engineered unit, it is compact to fit in tight spaces and provides multiple power receptacles and USB communications ports.



ADVANCED
REPLACEMENT
WARRANTY*



ION F-11 FEATURES:

- 3 year advanced replacement warranty*
- LCD display
- Boost and Buck Automatic Voltage regulation stabilises fluctuating power
- Easy battery replacement
- USB connection for local interface and communications
- Free software for real time monitoring and safe shutdown of connected equipment
- Auto-charge even when UPS is off
- Auto-restart in AC power recovery
- Modem/phone line surge protection
- Discharge, overcharge and overload protection

*3 year advanced replacement warranty on electronics and batteries. See website for full terms and conditions.

Contact an ION technical expert

EMAIL: info@ionups.com.au WEB: www.ionups.com.au PHONE: 1300 700 805

SPECIFICATIONS: ION F-11

MODEL		F11-650VA	F11-1200VA	F11-2200VA
CAPACITY	VA	650VA	1200VA	2200VA
INPUT	Voltage		Variable 170 - 280VAC	
	Normal Frequency		50Hz	
OUTPUT	Voltage		Variable 220-240VAC	
	Frequency		50Hz ±5Hz	
	Output Waveform		Modified Sinewave	
	Connections	2 X Australian 3 pin 10A	4 X Australian 3 pin 10A	4 X Australian 3 pin 10A
EFFICIENCY	Line Mode		> 95%	
	Battery Mode		60%	
TRANSFER TIME	BAT <--> LINE	2-6ms	4-8ms	4-8ms
BATTERY	Typical Recharge Time		6 hours to 90%	
USER INTERFACE	Display		LCD	
	Audible Alarm		Yes	
COMMUNICATION	Interface		USB	
ENVIRONMENT	Working Temperature		0-40°C	
	Noise Level	<40dB	<45dB	<45dB
WEIGHT AND DIMENSION	Net Weight	2.36kg	5.3 kg	5.93 kg
	Dimensions W x D x H (mm)	100 x 290 x 143	139 x 364 x 195	139 x 364 x 195



Contact an ION technical expert

EMAIL: info@ionups.com.au WEB: www.ionups.com.au PHONE: 1300 700 805